

Base Specifications

1" Aluminum Standard Cordless



Headrail: 1" high by 1-1/2" decorative Steel headrail. Phosphate coated vinyl primered finished with a polyester baked enamel.

Bottom Rail: C shaped rail, phosphate coated and vinyl primered finished with a polyester baked enamel. Bottom Rail is color coordinated with slats.

Slats: Cold rolled spring tempered virgin aluminum slat. To have normal width of 1" and be 0.006" thickness after paint, to provide maximum strength and flexibility. Slats to be finished with a polyester baked enamel. 8g slats are available.

Tilter: The tilter shall be worm gear design and shall be in an enclosed housing and secured by means of steel rivets to prevent separation. The stem shall be made of clear polycarbonate, the gear of polyacetal and the housing of clear polycarbonate, prelubed prior to assembly to assure durability and ease of use.

Tilt Wand: Tilt wand should be plastic measuring approximately 5/16", fluted with grooves for a non-slip grip.

Cordless Modules: Cordless modules are constructed with PVC body. Lift cord is wound inside the module. Steel spring provides tension to pull the blind up. Lift cord is white color.

Ladders: Braided polyester with spacing of not more than 0.865" and arranged for total support of slat. Ladders are color coordinated with slats.

Installation Brackets: Constructed of cold rolled steel. Zinc plated. Hex head screws are included.

Cordless Handle: 100% PVC

Fire Safety: Blind materials have been tested in accordance with the procedures outlined in NFPA 701 Fire Test 1.